



# 38 METER ZZ-FOLD

5 SECTION

BOOM PUMP



JXZZ 38-5.16\*

## BOOM SPECIFICATIONS

Vertical Reach	37.5 m (123')
Horizontal Reach	33.5 m (109'11")
Reach from Front - Cabover	30.5 m (100'1")
Unfolding Height	7.3 m (23'11")
1st Section Length	7.8 m (25'7")
2nd Section Length	6.1 m (20')
3rd Section Length	6.3 m (20'8")
4th Section Length	6.6 m (21'8")
5th Section Length	6.7 m (22')
Outrigger	X-Style
Front Spread	6.0 m (19'8")
Rear Spread	7.8 m (25'7")

## GENERAL SPECIFICATIONS

Pipe Size (ID)	125 mm (5")
Boom Control Valve	Proportional (by HAWE)
Radio Remote:	Dual Wireless Transmitter System
Vibrator	Standard
Water Pump	Hydraulic Power 20 bar (290 psi)
Water Tank	800 L (211 G)
Wear Parts	Carbide
Popular Upgrades†	LED Boom Light Kit LED Outrigger Lights Heated Water Tank Heated Hydraulic Tank Air-Cuff Twin Wall Pipe 18 or 20 cell Pump Kit Big Mouth S-Tube

†more options available, ask your sales rep for details.

## PUMP SPECIFICATIONS

Output	Rod Side	164 m³/h (215 yd³/h)
	Piston Side	102 m³/h (133 yd³/h)
Pressure	Rod Side	72 bar (1044 psi)
	Piston Side	115* bar (1668 psi)
Concrete Cylinder Diameter	230 mm (9")	
Concrete Cylinder Type	Hard Chromed	
Stroke Length	2100 mm (83")	
S-Tube Size	8" X 7"	
Main Oil Pump	Rexroth Hydromatic A11VSO260	
Hydraulic System Pressure	350 bar (5076 psi)	
Lube System (Hopper)	Automatic	
Switching System	Hydraulic	
Hopper Capacity	Easy Clean 600 L (158 G)	
Number of Strokes/Min	31	
Output Control Range	10(13)~164m³/h(215yd³/h)	

\*Not to be used through boom pipe.

\*Contact your sales representative for alternate chassis options.

[www.allianceconcretepumps.com](http://www.allianceconcretepumps.com)



# JXZZ 38-5.16

## BOOM PUMP



1.888.584.7231



1.888.870.0908

Reach from front : 30.5m (100'1")



## DIAGRAMS

